


Wall Mount TRANSMITTER



Features

- Code-Hopping Encryption
- Audible Piezo output
- Weather-proof / Splash-proof housing
- CR2450 3V Lithium battery
- Expected +/- 30,000 Activations
- Frequency stability controlled +/- 75KHz



Inside view

Applications

- Under counter Panic button
- Nursing home Panic button
- Bathroom Panic button
- Shower Panic button
- Door release button
- Door bell button

Specification:

Encryption:	Code-Hopping
Range "Line of site":	150m
Range "Indoors":	40m
Frequencies available:	403MHz / 433MHz
Voltage Range:	2.2V to 4.5V DC
Current on TX:	+/-12 mA
Sleep mode:	+/-400 nA
Dimensions:(lxbxh)	60x60x25mm
Gross Weight:	55 grams
Operating Temp:	-3°C to 65°C
Warranty:	24 Months

Order Codes

1 Ch Wall mount Transmitter	WMTX
3V Lithium Battery CR2450	CR2450
Spare WMTX Casing ABS	WM_ABS

Certifications

- ETSI EN300 220-V2.4.1
- ETSI EN301-489-3 V1.4.1
- ETSI EN301-489-1 V1.9.2
- IEC 60950-1:2005 + A1:2009
- ICASA: TA-2014/2629